

# StyleLite® TruGloss Cleaning Guide

## Step 1:

Use warm soapy water and a clean microfiber cloth to wipe the surface sheet in a back-and-forth motion until the mark is removed. Dry gently with a clean microfiber cloth.



## Step 2:

Use Vuplex® or Matte Maxx® regularly to maintain your StyleLite finish.



**⚠ DO NOT APPLY THE PRODUCT DIRECTLY TO THE SHEET.** Apply the recommended cleaning product to a damp microfiber cloth and then clean the sheet as instructed in step one.



## Step 3:

If the mark persists, you can use one of the cleaning products listed below.

**ALWAYS** wipe the face sheet down with a damp clean microfiber cloth after you are finished in order to remove residue that could damage the sheet.

- ✓ Sugar soap
- ✓ Low odor kerosene
- ✓ 9:1 water to Isopropyl Alcohol (IPA) mix.

## NEVER USE:

- × Edge band glue cleaner\*
- × Acids (citric, hydrochloric, sulfuric...etc.)
- × Products containing solids or abrasives (oven cleaner, drain cleaner, bleach, toothpaste...etc.)
- × Alcohols (ethanol, methanol, highly concentrated IPA, etc.)
- × Nail polish remover (acetone and acetone-free)
- × General cleaner (e.g., BAM)
- × Synthetic oils/lubricants
- × Disinfectant sprays (e.g., Lysol, Clorox, Glen 20)
- × Brushes, scourers, or abrasive cleaning clothes
- × Abrasive cleaners
- × Thinners or methylated spirits



\*Edge band cleaners (ABS cleaners) are to **never be used** on StyleLite, including during edge-banding. The protective film adhered to the StyleLite sheet **must stay on during edge-banding**. The film must also stay on during all processing of the sheet until it is fully installed to prevent scratching.

This is not a comprehensive list of unsuitable cleaning products, and various other chemicals are not compatible with StyleLite products.

## Scratch Removal for TruGloss

### Removing Marks and Light Scratches - Gloss Only

Apply Novus® No. 2 or a good quality liquid polish (e.g., 3M™ Finesse-It™ II, Kitten® Polishing Wax) and using a damp, clean microfibre or soft cloth, polish in a circular pattern. Then remove polish using the cleaning procedure in step one.



### Removing Heavier Scratches - Gloss Only

Apply Novus® No. 3 or a good quality fine compound polish (e.g., 3M™ Perfect-It™ III) and using a damp, clean microfibre or soft cloth, polish in back-and-forth motion at right angles to visible scratches. Then use Removing Marks and Light Scratches procedure.

Ensure all polish residues are removed completely from the StyleLite surface. Low speed electric buffing can also be used to repair marks and scratches on gloss sheet and panels.

